











BF 030 AG-CF 031 AG Θάλαμοι ταχείας κατάψυξης

(με ενσωματωμένο ψυκτικό μηχάνημα)











Τεχνικά χαρακτηριστικά

BF 030 AG

-  Χωρητικότητα: 3 GN 2/3 (35,3 x 32,5 cm)
-  Απόδοση / ώρα { (+90°C / +3°C): 8 Kg
{ (+90°C / -18°C): 5 Kg
-  Ισχύς: 587 W
-  Ψύξη: Βεβιασμένης κυκλοφορίας
-  Φρέον: R 452 A
-  Τάση: 230V - 50Hz - 1ph
-  Βάρος: 47 kg
-  Διαστάσεις: 56 x 56 x 52 cm
(μήκος x βάθος x ύψος)

CF 031 AG

-  Χωρητικότητα: 3 GN 1/1 (53 x 32,5 cm)
-  Απόδοση / ώρα { (+90°C / +3°C): 8 Kg
{ (+90°C / -18°C): 5 Kg
-  Ισχύς: 587 W
-  Ψύξη: Βεβιασμένης κυκλοφορίας
-  Φρέον: R 452 A
-  Τάση: 230V - 50Hz - 1ph
-  Βάρος: 52 kg
-  Διαστάσεις: 56 x 70 x 52 cm
(μήκος x βάθος x ύψος)

Βασικός εξοπλισμός: ο ανοξείδωτος φοριαμός στήριξης λαμαρινών και 3 πλαστικοποιημένες σχάρες GN